

A 10 basic

Analytical grinder

- With a built-in cooling chamber
- Suitable for low-loss dry grinding of soft, hard and brittle substances
- Removable, easy-to-clean, high-grade steel chamber
- 3 interchangeable cutters available
- Electronic overload protection

Max. task granularity	6 - 7 mm
Nominal speed	20.000 min ⁻¹
Effective vol. of grinding chamber	50 ml
Duty cycle ON / OFF	5 min / 10 min
Dimensions (W x D x H)	120 x 105 x 225 mm
Weight	2,2 kg
Protection class acc. to DIN EN 60529	IP 21



A 10 basic incl. A 14 and A 18

1.097,00 EUR

Ident. No. 3250000

A 14 (included with delivery)	Ident. No. 1059300	22,00 EUR
A 18 (included with delivery)	Ident. No. 2318200	48,00 EUR
A 15	Ident. No. 1059100	121,00 EUR
A 17	Ident. No. 1462700	59,00 EUR

Stainless steel cutter A 14
For pulverizing most brittle materials, suitable for Mohs hardness up to 5 (included with delivery).



Grinding chamber reduction A 18
For pulverizing only very small test samples (included with delivery).

Hard metal cutter A 15
Made of tungsten carbide for hard materials suitable for Mohs hardness up to 9.



Star-shaped cutter A 17
Suitable to grind fibrous substances such as paper and dried vegetation, soil samples, frozen meat and plastic granulates with low volume weight.

IKA®-WERKE GMBH & CO.KG