

www.imlab.eu

info@imlab.eu - Tél. : +32 (0)16 73 55 72

imLab

www.imlab.fr

info@imlab.fr - Tél. : +33 (0)3 20 55 19 11

Imlab sprl - Oude Vijvers, 1
3370 Boutersem - Belgique

Imlab sarl - Centre d'Affaires de l'Horlogerie
48 rue des Canonniers - 59000 Lille - France



Hielscher Ultrasonics

High-Power
Ultrasonic
Devices for
Lab and
Industry



Hielscher Ultrasonics– Your Expert for Ultrasonic Processes

Hielscher Ultrasonics is the top supplier for high power ultrasound devices. Hielscher offers various ultrasonic processors for the use in lab, bench-top and industry. Important applications are homogenizing, emulsifying, dispersing, de-agglomeration as well as the sonochemistry and sono-catalysis.

Ultrasonic Homogenizing:

Hielscher homogenizers are very efficient for the reduction of soft and hard particles. By intense cavitation forces, ultrasound reduces small particles (solids or liquids) in a liquid to improve uniformity and stability.

Ultrasonic Emulsifying:

Emulsions are dispersions of two or more immiscible liquids. Highly intensive ultrasound supplies the power needed to disperse a liquid phase (dispersed phase) in small droplets in a second phase (continuous phase). In the dispersing zone, imploding cavitation bubbles cause intensive shock waves in the surrounding liquid and result in the formation of liquid jets of high liquid velocity. As ultrasonication can produce very small droplets of almost uniform size in batch and production process, ultrasound is an effective method to create stable emulsions and even microemulsions.



Ultrasonic Dispersing & Deagglomeration:

The dispersing power of ultrasound is well-known and a reliable and efficient method to mix powders into liquids. High power ultrasound grinds and deagglomerates particles held together by attraction forces of physical and chemical nature down to micron and nano size and disperses the individual particles fine and evenly in the liquid. Generally, ultrasound produces very narrow particles size distribution.

Sono-Chemistry:

Sonochemistry is the application of ultrasound to chemical reactions and processes. The mechanism causing sonochemical effects in liquids is the phenomenon of acoustic cavitation.

High power ultrasound



- increases the reaction speed and reaction output,
- provides a more efficient energy usage,
- improves the performance of phase transfer catalysts or makes an avoidance of phase transfer catalysts possible,
- increases the reactivity of reagents or catalysts,
- offers sono-chemical means for switching of the reaction pathway,
- enables to use crude or technical agents,
- and activates metals and solids.

Sono-Catalysis:

Ultrasonication affects the catalyst reactivity during catalysis by enhanced mass-transfer and energy input. In heterogeneous catalysis, where the catalyst is in a different phase to the reactants, ultrasonic dispersion increases the surface area available to the reactants. Ultrasonication contributes to heterogeneous and homogeneous catalysis in many ways. Cavitation erosion on particle surfaces generates unpassivated, highly reactive surfaces. Short-lived high temperatures and pressures contribute to molecular decomposition and increase the reactivity of many chemical species. Ultrasonic irradiation can be used in the preparation of catalysts, e.g. to produce aggregates of fine-size particles.





Ultrasonic Lab Device UP50H

Ultrasonic Lab Device UP50H		
	UP50H - compact light-weight ultrasonic device	UP50H at stand ST1-16
Technical Details	UP50H: Compact ultrasonic lab device (50W, 30kHz) for handheld and stand-mounted operation, automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, dry running protected, with 9-pin DSUB interface, light-weight, in portable case, IP40 grade, titanium horn	
Applications	Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Wet-milling, Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry	
Advantages	<p>Performance: With 50 watts power, the UP50H is much more powerful than an ultrasonic bath or tank.</p> <p>Flexibility: For handheld or stand-mounted use, with various accessories for optimal adaption to your process.</p> <p>Quality: The UP50H device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.</p>	

Items:

- Ultrasonic Processor UP50H ◦ 115 volts ◦ 230 volts
- Sonotrode MS3 (tip diameter 3mm)
- Sonotrode MS7 (tip diameter 7mm)
- Stand ST1-16
- ST1-Clamp
- PowerMeter PowMet ◦ 115 volts ◦ 230 volts



Ultrasonic Lab Device UP100H

Ultrasonic Lab Device UP100H	 <p>UP100H - compact light-weight ultrasonic device</p>	 <p>UP100H at stand ST1-16</p>
Technical Details	UP100H: Compact ultrasonic lab device (100W, 30kHz) for handheld and stand-mounted operation, automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, dry running protected, with 9-pin DSUB interface, light-weight (1.1kg), in portable case, IP40 grade, titanium horn	
Applications	Sample Preparation, Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Wet-milling, Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry	
Advantages	<p>Performance: With 100 watts power, the UP100H is much more powerful than an ultrasonic bath or tank.</p> <p>Flexibility: For handheld or stand-mounted use, with various accessories for optimal adaption to your process.</p> <p>Quality: The ultrasonic lab device UP100H fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.</p>	

Items:

- Ultrasonic Processor UP100H ◦ 115 volts ◦ 230 volts
- Sonotrode MS3 (tip diameter 3mm)
- Sonotrode MS10 (tip diameter 10mm)
- Stand ST1-16
- ST1-Clamp
- PowerMeter PowMet ◦ 115 volts ◦ 230 volts

Ultrasonic Device UP200Ht

<p>Ultrasonic Device UP200Ht</p>	 <p style="text-align: center;">UP200Ht – comfortable use as handheld homogenizer</p>	 <p style="text-align: center;">UP200Ht with acrylic sound protection box</p>
<p>Technical Details</p>	<p>UP200Ht: 200 watts, 26kHz; for handheld and stand-mounted use; automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, with colored touch-screen & digital control, operation and control via LAN, automatic data recording, dry running protected, IP41 grade, titanium horn \varnothing 10mm, amplitude at horn 70μm, in portable case</p>	
<p>Application</p>	<p>Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry</p>	
<p>Advantages</p>	<p>Performance: With 200 watts power, the UP200Ht is much more powerful than an ultrasonic bath or tank.</p> <p>Flexibility: For handheld or stand-mounted use, with various accessories for optimal adaption to your process.</p> <p>Comfortable Operation: The light-weight device is ergonomically designed. The operation settings can be adjusted via the colored touch-screen. All functions are easily and intuitively reachable through one main menu.</p> <p>Quality: The UP200Ht device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.</p>	



Items:

- Ultrasonic Processor UP200Ht \circ 115 volts \circ 230 volts
- Sonotrode S26d2 (tip diameter 2mm)
- Sonotrode S26d7 (tip diameter 7mm)
- Sonotrode S26d14 (tip diameter 14mm)
- Stand ST1-16
- Sound Protection Box SPB-L, made from acryl glass



color touch-screen

Ultrasonic Device UP200St



<p>Ultrasonic Device UP200St</p>	 <p style="text-align: center;">UP200St – digital homogenizer with acrylic sound protection box</p>	 <p style="text-align: center;">UP200St for stand-mounted and hand-held use</p>
<p>Technical Details</p>	<p>UP200St: 200 watts, 26kHz; for handheld and stand-mounted use; separated generator and transducer (UP200St-T + UP200St-G) fulfilling IP51 + IP65 grade, automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, with colored touch-screen & digital control, operation and control via LAN, automatic data recording, dry running protected, titanium horn \varnothing 14mm, amplitude at horn 70μm, in portable case</p>	
<p>Applications</p>	<p>Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry & Sono-Catalysis</p>	
<p>Advantages</p>	<p>Performance: 200 watts power, very reliable & robust device for heavy duty operation</p> <p>Flexibility: Handheld or stand-mounted use, with various accessories for optimal adaption to your process.</p> <p>Comfortable Operation: The separated design of transducer and generator allows to place the generator safely outside the operation area.. The operation settings can be adjusted via the colored touch-screen. All functions are intuitively reachable through one main menu.</p> <p>Quality: The UP200St device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.</p>	

Items:

- Ultrasonic Device UP200St (generator + transducer)
- Sonotrode S26d2 (tip diameter 2mm)
- Sonotrode S26d7 (tip diameter 7mm)
- Sonotrode S26d14 (tip diameter 14mm)
- Stand ST1-16
- Sound Protection Box SPB-L, made from acryl glass



Digital Ultrasonic Device UIP200St and VialTweeter

<p>Ultrasonic Processor UP200St with VialTweeter</p>	 <p>UP200St with VialTweeter</p>	 <p>UP200St-T, VialTweeter & VialPress</p>
<p>Technical Details</p>	<p>UP200St processor: 200 watts digital ultrasonic processor, with touch display and automatic data recording, ultrasonic frequency 26kHz (auto scan), countdown (timer): 0.1sec to 99 days, shutdown when final energy input reached (Ws, Wh, kWh), autom. calibration of the amplitude-dependent idle power, data recording: amplitude, power, time, temperature on internal SD-Card (1GB), display and remote control via browser on PC/MAC without software installation, remote control via PLC</p> <p>VialTweeter: S26d11x10 block sonotrode, stainless steel, for UP200St, simultaneous sonication of up to 10 EppendorfVials, for vials and test tubes of 0.5ml, 1.0ml, 1.5ml or 2.0ml volume, e.g. 12x32mm or 15x45mm, other vial sizes available on request</p>	
<p>Applications</p>	<p>Sample Preparation, Mixing & Blending, Homogenization, Emulsifying, Dispersing & Dissolving, Disintegration & Cell Disruption, Deagglomeration & Particle Size Reduction, Degassing</p>	
<p>Advantages</p>	<ul style="list-style-type: none"> • Performance: up to 10 watts into each of the ten vials • Efficiency: <ul style="list-style-type: none"> - higher efficiency than ultrasonic bath or tank as the energy goes only into the liquid in the vials -time saving: the power levels allow for sophisticated sonication processes in short time, similar to direct sonication by a homogenizer -simultaneous sonication of up to 10 vials under same conditions • Flexibility: <ul style="list-style-type: none"> - the ultrasonic processor UP200St can be used with VialTweeter for indirect sonication or with sonotrode for direct probe sonication - various accessories allow use in manifold applications and conditions - VialTweeter is suitable for vials of the most common sizes, brands and designs. Possibility for indirect sonication of a single vessels with up to 500ml with the mountable VialPress 	

Items:

- Ultrasonic Processor UP200St o 115volts o 230volts
- VialTweeter S26d11x10 block sonotrode
- VialPress



Digital Ultrasonic Device UP400St (400 watts, 24kHz)



<p>Stand-mounted Ultrasonic Device UP400St</p>	 <p>UP400St 400 W powerful ultrasonicator</p>	 <p>The UP400St features a color touch-display, SD-card slot, LAN port and temperature sensor</p>
<p>Technical Details</p>	<p>UP400St: 400 watts, 24kHz; for stand-mounted use; automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, with colored touch-screen & digital control, operation and control via LAN, automatic data recording, dry running protected, IP41 grade, titanium horn, in portable case</p>	
<p>Applications</p>	<p>Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Wet-milling & Grinding (e.g. nano materials), Emulsifying, Lysis & Cell Disintegration, Extraction, Sonochemistry</p>	
<p>Advantages</p>	<p>Effectiveness: High-power lab device for sonication of larger volumes from 5 mL up to 4L in the batch and approx. 10 to 50 litres per hour with flow cell.</p> <p>Flexibility: Beaker sonication and continuous sonication for applications in lab & bench-top scale and for small production.</p> <p>Simplicity: The operation settings can be adjusted via the colored touch-screen. All functions are easily and intuitively reachable through one main menu. The UP400St is simple to use and easy to clean.</p>	

Items:

- Ultrasonic Processor UP400St ◦ 115 volt ◦ 230 volt
- Sonotrode S24d7 with 7mm tip diameter
- Sonotrode S24d14 with 14mm tip diameter
- Flow Cell FC22K stainless steel, volume approx. 15ml
- Sonotrode S24d22D with seal for flow cell FC22K
- Stand ST1-16
- Sound Protection Box SPB-L, made from acryl glass



SonoStep – Multi-Functional Ultrasonic Device with integrated Stirring and Pumping Functions

<p>Ultrasonic Device UP200St-TD with SonoStep</p>	 <p style="text-align: center;">generator UP200St + transducer TD + top piece SonoStep</p>	 <p style="text-align: center;">TD + SonoStep for combined pumping, stirring & sonication</p>
<p>Technical Details</p>	<p>The SonoStep is the perfect device for reliable and comfortable sample preparation. The three essential functions of continuous sonication, stirring and pumping are integrated in a compact device. Ultrasound, and centrifugal pump are integrated into an agitated stainless steel beaker.</p> <p>The 200 watts digital ultrasonic generator is equipped with touch display and automatic data recording, ultrasonic frequency 26kHz (auto scan); countdown timer, shutdown when final energy input reached (Ws, Wh, kWh); auto-calibration of the amplitude-dependent idle power; data recording: amplitude, power, time, temperature on internal SD-Card; display+remote control via browser on PC/MAC without software installation, remote control via PLC.</p>	
<p>Applications</p>	<p>Small Volume Processing & Sample Preparation before Analysis: Sonication, Stirring and Pumping in one device</p>	
<p>Advantages</p>	<ul style="list-style-type: none"> • Performance: <ul style="list-style-type: none"> - Consistent sonication with up to 200 watts for sample preparation. - The SonoStep pumps, stirres and sonicates the sample in recirculation. - Mixing/ Dispersing/ Deagglomeration + De-aeration by Power Ultrasound - Direct connection to the analytical device for most accurate measurements. - No sample loss, no cross-contamination • Efficiency: <ul style="list-style-type: none"> - effortless sample preparation by simple setup and operation of one device - time saving: the power levels allow for sophisticated sonication in a short time, similar to direct sonication by a homogenizer with the advantage that the SonoStep delivers the sonicated sample directly to the analytical device - direct connection of the SonoStep with the analytical device, e.g. for particle measurement • Flexibility: <ul style="list-style-type: none"> - Simple setup and operation - Quick-locking mechanism for fast and simple cleaning - Simply exchanable hose or pipe connections - Cuphorn and flow cell for specific applications are additionally available 	

Hielscher Ultrasonics

Bench-top & Industrial Ultrasonic Systems

- UIP500hdT (500W)
- UIP1000hdT (1 kW)
- UIP1500hdT (1.5 kW)
- UIP2000hdT (2 kW)
- UIP4000hdT (4 kW)
- UIP16000 (16 kW)



UIP2000hdT – Powerful Industrial Ultrasonic Device

Ultrasonic Processor
UIP2000hdT



UIP2000hdT transducer and generator



UIP2000hdT installation

Technical Details

Ultrasonic processor UIP2000hdT (2000W, 20kHz) consisting of transducer and generator; digital control, color touch display, intelligent data recording on internal SD card, automatic frequency tuning, amplitude 25 micron, amplitude adjustable from 20 to 100%, dry running protected, remote control via browser on PC or MAC without software installation, transducer IP65 grade, titanium horn

Applications

Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Wet-milling & Grinding (e.g. nano materials), Emulsifying, Lysis & Cell Disintegration, Extraction, Sonochemistry & Sonocatalysis


Advantages

Effectiveness: High-power, high performance ultrasonic device with 2000 watts power, various recirculation setups for continuous processing,
Reproducibility: Exact reproducibility by full control over the parameters „ Amplitude, Pressure, Temperature, Viscosity, and Concentration“
Scalability: All results achieved can be scaled up linearly.
Industrial Grade: Full industrial grade, for heavy-duty operation and permanent use 24 hours per day (24h/7d), scale-up by cluster installation

Items:

- Ultrasonic processor UIP2000hdT
 - o 115 volts o 230 volts
- Sonotrode BS4d34 (tip diameter 34mm)
- Sonotrode BS4d40 (tip diameter 40mm)
- O-Ring-Flange RFLA100
- Flow Cell FC100L1-1S w/ cooling jacket
- Flow Cell Insert34
- Booster Horn B4-2
- Stand ST2
- Sound Enclosure

browser control PC/MAC/Smartphone



SonoStation - Hielscher's pump solution

Features:

- easy-to-use
- easy-to-clean
- fully integrated
- simple setup
- small footprint
- holds up to 4kW sonication power (2x UIP500 to UIP2000hdT)
- robust for everyday use (pilot or production)
- flexible for process development
- stainless steel tank
- no sedimentation as in horizontal pumps

Technical Details:

- stainless steel
- 230VAC or 115VAC single phase for standard wall outlet
- Progressive cavity pump for constant flow and constant pressure
- with VFD, 40 to 495RPM
- 15-180L/h
- max 5barg
- self priming
- high viscosity, even grout

Ultrasonic processing is just one step in your process development or everyday production. The installation and operation of the ultrasonic reactor should be as simple as possible. The SonoStation is an easy-to-use pumping system to move your liquid material to the ultrasonic reactor at constant flow and constant pressure. We integrated a 38L stirred tank (jacketed) with a progressive cavity pump into a mobile processing system. We even included a stand for up to two ultrasonic reactors. This high level of integration reduces the number and size of wetted parts, fittings and connectors. This makes the SonoStation easier to use and easier to clean than a conventional setup. It reduces the footprint too.

